BA Green Flash 5R

5 Mil Polyester Film



Description:

BA Green Flash 5R is a durable polyester tape that is often used for puncture and damage resistance. BA Green Flash 5R has excellent bonding properties to a white variety of substrates like treated papers, films and foils. BA Green Flash 5R is suitable for splicing g applications, including oven splices when wet out capabilities are important. Green Flash 5R non-silicone adhesive eliminates silicone contamination and is specially formulated to remove cleanly from most surfaces after up to 4 hours at 350°F.

Features & Benefits:

- Conformable
- Clean removal
- Durable
- Temperature resistant

Applications:

Composite bonding, flash breaking and protecting

Holding and positioning

Construction/ Typical Properties	Value	
Color(s):	Green	
Adhesive:	Rubber	
Backing:	Polyester Film	
Elongation at Break:	100%	
Dielectric Strength:	10,000 volts	
	Imperial	Metric
Adhesive Thickness:	2 mils	51 µm
Backing Thickness:	5 mil	127 µm
Total Thickness:	7 mils	178 µm
Tensile Strength:	100 lb/in	175 N/cm
Adhesion to Steel:	6.4 oz/in	0.7 N/cm
Max Operating Temperature:	0 to 325°F	0 to 163°C
Insulation Class:	130°C	

The physical properties listed above are typical values and are not to be construed as specifications. Our suggestions and recommendations for use are based on tests we believe to be reliable. Bron Aerotech does not warrant that the product is fit for any particular purpose. Purchaser must determine suitability of the product for the intended use. Bron Aerotech, Inc. assumes no liability for claims beyond the replacement value of our product proved to be defective. Manufactured for and distributed by Bron Aerotech.

Copyright© Bron Aerotech
Last Updated: 9/10/2026